



UltraFire



Radio-Interlinked Battery Heat Alarm

Why do I need wireless? You cannot guarantee to hear your alarms from every room. With UltraFire wireless alarms, heat and smoke alarms can be interlinked into one system that will activate all sounders. When a fire in your kitchen triggers your heat alarm it will also sound the smoke alarm in your bedroom.



What features? Low battery is indicated with a chirp noise every 32 seconds with an LED flash. When silenced, the LED flashes every 8 seconds for 10 minutes. The batteries are user replaceable. Featuring a combined Test & Hush button, 8-10 hour "Do Not Disturb" function, and a 10 year warranty. Simple interlink

TECHNICAL DETAILS	DIMENSIONS (H x DIA)	40 x 102mm
	WEIGHT	0.18kg
	BATTERY TYPE	Replaceable 3V Alkaline (2 x AA)
	SENSOR TYPE	Thermistor
	SOUND OUTPUT	85dB+ at 3 metres
	HEAT SENSITIVITY	54°C – 70°C
	WIRELESS RANGE	Clear Line of Sight: 100m Typical Indoors: 35m
	INTERCONNECT LIMIT	50 devices
	SILENCE TIMEOUT	10 minutes
	DO NOT DISTURB TIMEOUT	8-10 hours
	CERTIFICATION	BS 5446-2: 2003
	SUITABILITY	BS 5839-6 Grade F2
	WARRANTY / LIFESPAN	10 years / 10 years
	PRODUCT CODE	UFUBH1RF

Why use a heat alarm?

Many places within the home are not suitable for smoke alarms. They can be falsely triggered by everyday vapours and fumes such as those from cooking, condensation, or even dust. Heat alarms detect temperature levels rather than smoke particles and are not susceptible to these problems. Use heat alarms in kitchens (but not directly above the cooker), boiler rooms, garages, and home workshops. Plus, outside the bathroom if the alarm goes off every time you have a shower!

Why UltraFire? Benefit from UltraFire's many years of experience and enjoy personal service, quality products and competitive trade pricing on a wide range of fire safety products.



Contact your UltraFire dedicated Account Manager for quality products at great prices

☎ 0800 612 6537 🖱 www.ultra-fire.co.uk ✉ support@ultra-fire.co.uk